



High Quality C18070 Chromium Zirconium Copper Rod Strip 1-50mm Or Customized Size Use For Industry

Our Product Introduction

Basic Information

- Place of Origin: china
- Brand Name: jinshunlai
- Certification: ISO, AISI, ASTM, GB, EN, DIN
- Model Number: 0.1mm-900mm
- Minimum Order Quantity: 1kg
- Price: Contact Us
- Packaging Details: Waterproof Paper, Steel Strip Packed and other Standard Export Seaworthy Package, or customized package
- Delivery Time: 5day
- Payment Terms: L/C, T/T , Western Union
- Supply Ability: 90000ton



Product Specification

- Application: Industrial
- Diameter: Customized
- Length: Customized
- Material: Chromium Zirconium Copper
- Shape: Rod
- Surface: Smooth
- Tolerance: $\pm 0.01\text{mm}$
- Standard: JIS ASTM DIN EN ISO



More Images



for more products please visit us on copper-solid.com

Product Description

High Quality C18070 Chromium Zirconium Copper Rod Strip 1-50mm Or Customized Size Use For Industry

Chromium zirconium copper is widely used in automobiles, motorcycles, barrels (cans) and other machinery manufacturing industry welding,

contact tips, switch contacts, mold blocks, welding machine aids with a variety of materials.

Industry-specific attributes

Cu (Min)	99.9%
Alloy Or Not	Is Alloy

Other attributes

Place of Origin	China
Application	industry, coin
Grade	Chromium Zirconium Copper
Model Number	C18070
Brand Name	JINSHUNLAI
Name	Chromium Zirconium Copper Strip
Product Name	C18070 Chromium Zirconium Copper Strip
Shape	Customised Shape
Type	Coil
Color	Red Coppery
Standard	JIS ASTM DIN EN ISO
Package	Fumigation Wooden Package
Length	Customer's Demands

Packaging & delivery

Package Type:	Standard seaborne waterproof packaging <input type="checkbox"/>
---------------	---

Supply Ability

Supply Ability	1000 Ton/Tons per month
----------------	-------------------------

ASTM		Chemical Comosition (%)				
		Cu+Ag	Cr	Si		
C18070		99.9 min	0.15-0.4	0.02-0.07		

Grade	Temper	HV	Tensile Strength (N/mm2)	Yield Strength (N/mm2)	Elongation (%)	Conductivity
C18070 (K75)	H02 (H/2)	120-150	400-480	no less than 300	no less than 8	no less than 82%
	H04 (H)	140-170	460-540	no less than 370	no less than 5	no less than 82%
	H06 (EH)	150-190	530-610	no less than 460	no less than 2	no less than 82%
	H08 (ESH)	-	550-630	no less than 520	no less than 7	no less than 79%



Wuxi Jinnuo copper Co.,Ltd



+86-17763564398



sales01@shuangheyisteel.com



copper-solid.com

32 Chengnan Road, New District, Wuxi City, Jiangsu Province, China